

0.6 / 1kV

# Servo Cables

PE/PVC 모터 전원공급용 / 구리망 씨드 / 0.6 / 1kV **SL 851 C**

**RoHS**



SAB D-VIERSEN SL 851 C 4 x 1,5 mm<sup>2</sup> CE RoHS

Marking for SL 851 C 08510415  
SAB BRÖCKSKES D-VIERSEN SL 851 C 4 x 1,5 mm<sup>2</sup> CE

## Construction (케이블구성)

<b>Conductor</b> (도체)	bare copper strands acc. to DIN VDE 0295 class 5+ IEC 60228 class 5 + HD 383 class 5
<b>Insulation</b> (내피재질)	PE 2Y11 acc. to DIN VDE 0207 part 2
<b>Core code</b> (코어식별)	coloured acc. to DIN VDE 0293 + HD 186 and a green-yellow earth wire
<b>Stranding</b> (도체연선)	in layers
<b>Wrapping</b>	PETP foil
<b>Screen</b> (씰드형식)	tinned copper braiding
<b>Wrapping</b>	non-woven tape
<b>Sheath material</b> (외피재질)	special PVC
<b>Sheath colour</b> (외피색상)	black (RAL 9005)

## Outstanding features (특징)

- ▶ low surface transfer impedance
- ▶ low mutual capacitance
- ▶ very good EMC characteristics

## Technical data (기술사양)

<b>Nominal voltage</b> (시용전압)	Uo/U 0.6/1 kV
<b>Maximum operating voltage</b> (최고 사용전압)	in three-phase current and single phase current operation : Uo/U 0,7/1,2 kV in D.C. current operation : Uo/U 0,9/1,8 kV peak value of alternating current : U <sup>1</sup> 1,7 kV
<b>Testing voltage</b> (시험전압)	4000 V core/screen 2500 V
<b>Min. bending radius</b> (곡률반경)	≤ 12 mm < 12 mm up to ≤ 20 mm > 20 mm fixed laying 5 x d 7,5 x d 10 x d flexible application 10 x d 15 x d 20 x d
<b>Radiation resistance</b> (내방사성)	8 x 10 <sup>7</sup> cJ/kg
<b>Temperature range</b> (사용온도)	-40 / +70°C fixed laying -20 / +70°C flexible application
<b>Fire performance</b> (내화성관련)	flame retardant and self-extinguishing acc. to IEC 60332-1
<b>Oil resistance</b> (내유성)	acc. to internal standard
<b>Chem. resistance</b> (내화학성)	별첨 참조
<b>Absence of harmfull substances</b>	acc. to RoHS-guideline 2002/95/ EG as well as Gefstoffv appendix IV-no. 24

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
08510415	4 x 1,50	0,25	10,7	107,5	173
08510425	4 x 2,50	0,25	12,3	164,2	242
08510440	4 x 4,00	0,30	14,3	221,2	328
08510460	4 x 6,00	0,30	16,2	330,6	455
08510470	4 x 10,00	0,40	20,0	514,1	711
08510480	4 x 16,00	0,40	25,7	768,6	1111
08510490	4 x 25,00	0,40	30,3	1228,2	1684
08510495	4 x 35,00	0,40	34,2	1624,7	2218

Other dimensions and colours are possible on request.



for DNC motors  
on frequency  
converters U<sup>1</sup> 1.7 kV

