



High Flexible cables for power chain application

S 90 연속적 움직임 / PUR 데이터 케이블 / 숫자코어

SAB BROCKSKES D-VIERSEN S 90 VDE Reg.-Nr. CE RoHS

RoHS

Aufdruck-Beispiel für S 90 07780715
SAB BROCKSKES D-VIERSEN S 90 VDE Reg.-Nr. 7621 7 x 1,5 mm² CE

Construction (케이블구성)

Conductor (도체)	bare copper strands acc. to DIN VDE 0295 class 6 + IEC 60228 class 6 + HD 383 class 6
Insulation (내피재질)	PVC, T12 acc. to DIN VDE 0281 part 1 + HD 21.1
Core code (코어식별)	black cores with consecutive numbers acc. to DIN VDE 0293 + HD 21.1; green-yellow earth wire from 3 cores
Stranding (도체연선)	specially adjusted layering with non-woven tape over the outer layer
Sheath material (외피재질)	TMPU acc. to DIN VDE 0282 part 10 + HD 22.10 with mat surface
Sheath colour (외피색상)	grey (RAL 7000)

Outstanding features (특징)

- ▶ very good EMC characteristics (탁월한 EMC기능)
- ▶ improved abrasion resistance (내 마모성 강화)
- ▶ high tear resistance (피복강화-뺨겨지지 않음)
- ▶ good chemical resistance (국 내화학성)
- ▶ increased efficiency (향상된 품질)

Technical data (기술사항)

Nominal voltage	U ₀ /U 300/500 V
Testing voltage	3000 V acc. to DIN VDE 0281 part 2 + HD 21.2
Min. bending radius(곡률반경) continuously flexible	7.5 x d
Radiation resistance(내방사성)	8 x 10 ⁷ cJ/kg
Temperature range (사용온도) fixed laying flexible application	-40 / +70° C + 5 / +70° C
Fire performance(내화성관련)	flame retardant and self-extinguishing acc. to IEC 60332-1 + EN 50265-2-1 + VDE 0482 part 265-2-1
Oil resistance (내유성)	very good - TMPU acc. to DIN VDE 0282 part 10 + HD 22.10
Chem. resistance (내화학성)	good against acids, alkalines, solvents, hydraulic liquids etc.
Flexibility(유연성)	very good

Also available as hybrid cable for example

3G1,0 + 16 X 0,34 mm²

3G1,0 + 8 X 0,34 mm²

1G0,5 + 4 X 0,34 mm²

Peak operating voltage of data conductors : max. 500V

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
07780205	2 x 0,50	0,16	5,3	9,6	32
07780305	3 x 0,50	0,16	5,6	14,4	40
07780405	4 x 0,50	0,16	6,0	19,2	48
07780505	5 x 0,50	0,16	6,5	24,0	58
07780705	7 x 0,50	0,16	7,6	33,6	81
07781205	12 x 0,50	0,16	9,2	57,6	115
07781805	18 x 0,50	0,16	11,1	86,4	175
07782505	25 x 0,50	0,16	13,2	120,0	230
07783605	36 x 0,50	0,16	14,7	172,8	319
07785005	50 x 0,50	0,16	18,0	240,0	452
07786505	65 x 0,50	0,16	20,2	312,0	583
07780207	2 x 0,75	0,16	5,8	14,4	40
07780307	3 x 0,75	0,16	6,1	21,6	51
07780407	4 x 0,75	0,16	6,6	28,8	61
07780507	5 x 0,75	0,16	7,2	36,0	76
07780707	7 x 0,75	0,16	8,5	50,4	106
07781207	12 x 0,75	0,16	10,6	86,4	160
07781807	18 x 0,75	0,16	12,4	129,6	233
07782507	25 x 0,75	0,16	14,7	180,0	305
07783607	36 x 0,75	0,16	16,9	259,2	441
07785007	50 x 0,75	0,16	20,1	360,0	602
07786507	65 x 0,75	0,16	22,6	468,0	778
07780210	2 x 1,00	0,16	6,0	19,2	46
07780310	3 x 1,00	0,16	6,3	28,8	59
07780410	4 x 1,00	0,16	6,9	38,4	73
07780510	5 x 1,00	0,16	7,5	48,0	90
07780710	7 x 1,00	0,16	8,8	67,2	126
07781210	12 x 1,00	0,16	11,0	115,2	191
07781810	18 x 1,00	0,16	12,8	172,8	275
07782510	25 x 1,00	0,16	15,7	240,0	382
07783610	36 x 1,00	0,16	18,0	345,6	547
07785010	50 x 1,00	0,16	21,0	480,0	732
07786510	65 x 1,00	0,16	23,7	624,0	963
07780215	2 x 1,50	0,16	6,6	28,8	58
07780315	3 x 1,50	0,16	7,0	43,2	78
07780415	4 x 1,50	0,16	7,6	57,6	97
07780515	5 x 1,50	0,16	8,3	72,0	120
07780715	7 x 1,50	0,16	10,2	100,8	175
07781215	12 x 1,50	0,16	12,3	172,8	259
07781815	18 x 1,50	0,16	14,4	259,2	380

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
07782515	25 x 1,50	0,16	18,0	360,0	533
07783615	36 x 1,50	0,16	20,1	518,4	746
07785015	50 x 1,50	0,16	23,9	720,0	1021
07786515	65 x 1,50	0,16	26,8	936,0	1321
07780225	2 x 2,50	0,16	8,4	48,0	93
07780325	3 x 2,50	0,16	8,9	72,0	125
07780425	4 x 2,50	0,16	10,1	96,0	163
07780525	5 x 2,50	0,16	11,1	120,0	201
07780725	7 x 2,50	0,16	13,2	168,0	285
07781225	12 x 2,50	0,16	16,4	288,0	431
07781825	18 x 2,50	0,16	19,7	432,0	650
07782525	25 x 2,50	0,16	23,9	600,0	879
07783625	36 x 2,50	0,16	27,2	864,0	1255
07780240	2 x 4,00	0,16	10,2	76,8	145
07780340	3 x 4,00	0,16	10,8	115,2	190
07780440	4 x 4,00	0,16	11,6	153,6	238
07780540	5 x 4,00	0,16	12,9	192,0	305
07780740	7 x 4,00	0,16	15,2	268,8	426
07781240	12 x 4,00	0,16	18,9	460,8	657
07782140	21 x 4,00	0,16	23,7	806,4	1134
07780260	2 x 6,00	0,21	12,5	115,2	218
07780360	3 x 6,00	0,21	13,2	172,8	286
07780460	4 x 6,00	0,21	14,4	230,4	364
07780560	5 x 6,00	0,21	15,9	288,0	461
07780660	6 x 6,00	0,21	18,7	345,6	581
07780760	7 x 6,00	0,21	18,7	403,2	642
07780361	3 x 10,0	0,21	15,9	288,0	416
07780461	4 x 10,0	0,21	17,3	384,0	570
07780561	5 x 10,0	0,21	19,1	480,0	724
07780661	6 x 10,0	0,21	21,0	576,0	835
07780362	3 x 16,0	0,21	18,6	460,8	664
07780462	4 x 16,0	0,21	20,3	614,4	849
07780562	5 x 16,0	0,21	22,4	768,0	1081
07780463	4 x 25,0	0,21	24,1	960,0	1247
07780563	5 x 25,0	0,21	26,7	1200,0	1601
07780464	4 x 35,0	0,21	27,5	1344,0	1665
07780564	5 x 35,0	0,21	30,4	1680,0	2140
07780465	4 x 50,0	0,30	32,5	1920,0	2354
07780565	5 x 50,0	0,30	36,5	2400,0	3066

Other dimensions and colours are possible on request.