

# 33SI

**+900 °C**

SILICA FIBRE BRAIDED SLEEVING  
NOT TREATED, NOT IMPREGNATED



## Standards\*

- IEC 60684-1 and 60684-2.

## Applications

- Protection of wiring harnesses or ducting subject to very high temperature.
- Industrial furnaces and air ovens.
  - Nuclear.

## Options

- Other diameters: contact us.
- Diameters > 20 mm: see SILIGAIN® GSIL.

## Packaging

- Diameters from 0.5 to 4 mm: 200 m spools.
- Diameters from 5 to 20 mm: 100 m spools.

## Characteristics

### General

- Continuous operating temperature: +900 °C.
- Peaks at: +1050 °C.
- Excellent thermal resistance.
- Excellent resistance to radiations.
- Low thermal expansion coefficient.
- High chemical resistance, especially to acids.
- Non-combustible.
- Good flexibility.
- Frays slightly when cut.

### Chemical

- Silicon dioxide: > 94 %.
- Product guaranteed asbestos free.

## Standard products

- Colour: white (natural).

### INTERNAL DIAMETER

### 33SI

Nominal value** (mm)	Approximate wall thickness (mm)	Approximate linear weight (kg/km)
0.5	0.20	4.7
1	0.20	5.6
1.5	0.20	6.3
2	0.20	7.8
3	0.20	9.6
4	0.30	15
5	0.30	20
6	0.30	24
7	0.30	27
8	0.30	30
10	0.40	36
12	0.40	48
14	0.40	66
16	0.40	80
18	0.40	88
20	0.40	94

For this product, please contact:

**OMERIN division principale** ✓

Zone Industrielle - F 63600 Ambert  
 Tél. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10  
 omerin@omerin.com

**OMERIN division silisol** ☐

BP 87 - ZI du Devey - F 42000 Saint-Étienne  
 Tél. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00  
 silisol@omerin.com

\*Standards: our products comply with all or part of the requirements of standards quoted; contact us.

\*\*The extra flexibility of this type of sleeving negates any need to show tolerances on the internal diameter.